# GL-32<sup>™</sup> Grease and GL-43<sup>™</sup> Oil Injectors

High-performance injectors for reliable machine lubrication

WEEEEEE

## Accurate, reliable and adjustable lubrication for every lube point on your machine

- Easy to design, setup and operate
- Flexible-add or subtract lube points without redesigning your system
- Versatile high performance-works with oil and grease grades to NLGI #2
- All injectors come standard with viton seals for use with synthetic lubricants and high temperature applications—up to 350° F (176° C)

Long life design outperforms the competition!



Precision-honed components for reliable operation in challenging environments







©2010 Graco Inc. Form No. 340575 Rev. B 2/11 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.

### Adjustable to fit any machine

#### **One Piece Cast Injector**

One piece design for added durability

#### **Output Adjustment Nut**


Adjustable output volume from 0.001–0.008 in<sup>3</sup> (0.02–0.13 cm<sup>3</sup>) makes it easy to customize each individual lube point

#### Visual Indicator Pin

Convenient front-mounted cycle pin indicator confirms that the injector is functioning properly

#### Fluoroelastomer Seals

Standard with Fluoroelastomer seals for use with synthetic lubricants and high temperature applications up to 350° F (176° C).



<b>Technical Specifications</b>	Grease	Oil	
Maximum operating pressure	3500 psi (241 bar) 1000 psi (69 bar)		
Minimum operating pressure	1200 psi (83 bar) 750 psi (52 bar)		
Typical operating pressure	1500 psi (103 bar)	850 psi (59 bar)	
Reset (vent) pressure	200 psi (13.7 bar)	150 psi (10 bar)	
Output volume per cycle (adjustable)	0.001–0.008 in <sup>3</sup> (0.02–0.13 cm <sup>3</sup> )		
Maximum temperature rating	350° F (176° C)		
Recommended fluids	Grease up to NLGI #2	Low Viscosity Lubricants*	
Instruction manual	313798		

\* Number 10 weight minimum

Ordering Information	GL-32 Carbon Steel Grease	GL-32 Stainless Steel Grease	GL-43 Carbon Steel Oil
Replacement Injector	24A920	24E390	24E245
1-Injector Manifold	24A921	24E391	24E241
2-Injector Manifold	24A922	24E392	24E242
3-Injector Manifold	24A923	24E393	24E243
4-Injector Manifold	24A924	24E394	24E244
Stand-Alone Injector	24A919	24E389	24E240
Repair Kit	24B360	24F944	24F201
Injector Outlet Replacement Kit (nut, ferrule and adapter)	24B677	24F943	24B667

### Contact us today!

To receive product information or talk with a Graco representative, call 800-533-9655 or visit us online at www.graco.com.